

AC Distribution Box

- AC, 3 Phase, 4 Wire, 433V, 50 Hz.
- Degree of Protection – IP 33, Indoor use.
- Incomer 100 Amp SFD.
- Outgoing 32A/16A, TP / DP MCBs.
- Wall/floor mounting type.
- Separate Instrument and Feeder Compartment.
- Suitable for power supply to yard lighting, battery charger, Substation equipment, compressors etc in 33 KV Substations.



L.T. Feeder Pillar

- 3 Ph, 440V, 50 Hz.
- Used for sub-distribution of electricity outdoors.
- 8/6/4/3/2 Way Construction, as per requirement.
- Rated Short circuit current – 16 kA for 3 seconds.
- 10 SWG (3.25 mm thick) construction.
- Front Compartment for HRC fuses and rear compartment for cable termination.
- Three position locking arrangement.
- Post Office Red paint (or as per requirement of customer).



H.T. Feeder Pillar

- 11 KV, 3 Ph, 50 Hz, 630A, AC rating.
- IP-54, outdoors construction.
- Suitable for outdoor electricity distribution at 11 KV, underground road crossing etc.
- 4 Way type, floor mounted.
- Insulation Level (Phase to Phase): 11 KV AC 50 Hz/18 KV AC 5 Hz (1 min withstand)
- Robust construction with 10 SWG (3.25 mm) fabrication.
- Rear side cable entry.

